

SWITCH TO GAS



DEWHOT

TYPE B

12L Constant Temperature Gas Geyser

NDCT12DH

This smart geyser automatically adjusts itself to the water flow. With multiple outlets running simultaneously your water temperature will always remain hot and constant regardless of the water demand.

- Requires no electricity - flame ignition and geyser function are battery operated
- Touch button temperature control
- 84% energy efficiency
- Gas efficient- reduces gas consumption according to flow demand
- Compatible with mixer taps
- Start up and geyser function operate on low water pressure
- Ventilation is required indoors
- Anti-freeze function
- Natural or LP gas compatible
- Flame failure safety device



For outdoor use under a cover with flue or indoor use with a flue (110mm)



Max Gas Pressure

2.8 kPa

Rated Input

24 Kw

Max Gas Consumption

1.44 Kg / hour

Water Pressure

25-500 kPa

Water Output (min/max)

3L - 12L / min

Unit Size

680 x 345 x 185 mm

Unit Weight

9.6 Kg

Packaged Size

715 x 400 x 240 mm

Packaged Weight

11.2 Kg

Gas Type

LPG/ NG

SWITCH TO GAS



DEWHOT



TYPE D

16L Constant Temperature Gas Geyser

NDCT16DH

This smart geyser automatically adjusts itself to the water flow. With multiple outlets running simultaneously your water temperature will always remain hot and constant regardless of the water demand.

- Touch button temperature control
- 84% energy efficiency
- Gas efficient - reduces gas consumption according to flow demand
- Anti-freeze function
- Start up/ geyser function can also operate on low water pressure
- Requires no electricity - flame ignition and geyser function are battery operated
- Compatible with mixer taps
- Flame failure safety device



For outdoor use under a cover



Max Gas Pressure

2.8kPa

Rated Input

32 Kw

Max Gas Consumption

2.3 Kg / hour

Water Pressure

25-500 kPa

Water Output (min/max)

4L - 16L / min

Unit Size

740 x 420 x 210 mm

Unit Weight

13.2 Kg

Packaged Size

865 x 485 x 270 mm

Packaged Weight

15.5 Kg

Gas Type

LPG