



6L Stainless Steel Camping Gas Geyser

JSD6DH

- Diaphragm activated
- Requires no electricity - flame ignition and geyser function are battery operated
- 84% energy efficiency
- Neat and compact
- Stainless steel cover
- LCD temperature display
- Flame failure safety device
- Anti-freeze function



TYPE D

For outdoor use under a cover



Max Gas Pressure

2.8kPa

Rated Input

12 Kw

Max Gas Consumption

0.96 Kg / hour

Water Pressure

50-500 kPa

Water Output (min/max)

3L - 6L / min

Unit Size

505 x 295 x 160 mm

Unit Weight

4.6 Kg

Packaged Size

565 x 355 x 185 mm

Packaged Weight

6 Kg

Gas Type

LPG



8L Stainless Steel Gas Geyser

JSD8DH

- Diaphragm activated
- Requires no electricity - flame ignition and geyser function are battery operated
- 84% energy efficiency
- Neat and compact
- Stainless steel cover
- LCD temperature display
- Flame failure safety device
- Anti-freeze function



TYPE D

For outdoor use under a cover



Max Gas Pressure

2.8kPa

Rated Input

16 Kw

Max Gas Consumption

1.24 Kg / hour

Water Pressure

50-500 kPa

Water Output (min/max)

4L - 8L / min

Unit Size

580 x 310 x 170 mm

Unit Weight

6.5 Kg

Packaged Size

650 x 390 x 215 mm

Packaged Weight

7.5 Kg

Gas Type

LPG/ NG



10L Stainless Steel Gas Geyser

JSD10DH

- Diaphragm activated
- Requires no electricity - flame ignition and geyser function are battery operated
- 84% energy efficiency
- Neat and compact
- Stainless steel cover
- LCD temperature display
- Flame failure safety device
- Anti-freeze function



TYPE D

For outdoor use under a cover



Max Gas Pressure

2.8kPa

Rated Input

20 Kw

Max Gas Consumption

1.55 Kg / hour

Water Pressure

50-500 kPa

Water Output (min/max)

5L - 10L / min

Unit Size

650 x 340 x 170 mm

Unit Weight

7.2 Kg

Packaged Size

710 x 395 x 205 mm

Packaged Weight

8.5 Kg

Gas Type

LPG



12L Stainless Steel Gas Geyser

JSD12DH

- Diaphragm activated
- Requires no electricity - flame ignition and geyser function are battery operated
- 84% energy efficiency
- Neat and compact
- Stainless steel cover
- LCD temperature display
- Flame failure safety device
- Anti-freeze function



TYPE D

For outdoor use under a cover



Max Gas Pressure

2.8kPa

Rated Input

24 Kw

Max Gas Consumption

1.86 Kg / hour

Water Pressure

50-500 kPa

Water Output (min/max)

6L - 12L / min

Unit Size

685 x 340 x 175 mm

Unit Weight

8.0 Kg

Packaged Size

710 x 395 x 210 mm

Packaged Weight

9.35 Kg

Gas Type

LPG



16L Stainless Steel Gas Geyser

JSD16DH

- Diaphragm activated
- Requires no electricity - flame ignition and geyser function are battery operated
- 84% energy efficiency
- Neat and compact
- Stainless steel cover
- LCD temperature display
- Flame failure safety device
- Anti-freeze function



TYPE D

For outdoor use under a cover



Max Gas Pressure

2.8kPa

Rated Input

32 Kw

Max Gas Consumption

2.65 Kg / hour

Water Pressure

50-500 kPa

Water Output (min/max)

8L - 16L / min

Unit Size

760 x 380 x 215 mm

Unit Weight

11.5 Kg

Packaged Size

845 x 436 x 260 mm

Packaged Weight

13.5 Kg

Gas Type

LPG